1000 Series Rustproof Vandal-Resistant Wall Luminaire



This wall bracket luminaire is as durable as it is attractive. Suitable for indoor/outdoor applications ranging from residential to commercial environments. **Rust resistant.** Engineered with components and materials offering the **highest resistance to corrosion and impact.** The **polycarbonate** housing is nonconductive, assuring more safety to the end user. Ideally suited as security lighting for homes, schools, motels, hospitals, condominiums and industrial, commercial, and government buildings.

Specifications

Lens:	Injection molded of UV-stabilized polycarbonate with threaded neck for twist-lock attachment. Average thickness is $1/8^{\circ}$. Smooth exterior surface for ease of cleaning.			
Bracket:	Ket: Injection molded in black, white, or bronze UV- stabilized, reinforced polycarbonate . Equipped with threaded cup for lens attachment.			
Housing: (optional)	Injection molded in black, white or bronze UV- stabilized, reinforced polycarbonate . Rear knockout for supply wire. Available with up to four threaded connections and plugs suitable for ¹ /2" conduit.			
Socket:	Medium-base high temperature phenolic with copper screw shell, rated at 250V, 660W, with leads insulated for 200°C.			
Lamp:	Uses a LED lamp. Provided by others.			
Hardware:	e: Optional Lens-Lock screws are 1/4-20 socket set screws. Mounting hardware included.			
Mounting:	Wall mounting only.			



SBA QUALIFIED SMALL BUSINESS MANUFACTURER

ICA TRADE AGREEMENT ACT COMPLIANT


ETL-US Listed For Wet Locations.

All polycarbonate components meet Underwriters Laboratories 746C tests for polymeric material and carry a flammability rating of 94HB or better on lenses and the superior 94-5V rating on housings.

Luminaire Type	
Catalog Number	
Job Name	
Approval	
••	



Exploded View and Dimensions





Shown With Opal White Lens

Shown With Optional Housing



Innovative Lighting Designs Since 1970

P.O. Box 5023, Monroe, NC 28111-5023, USA 704.283.7477 (HEADQUARTERS) • 800.842.9345 (TOLL FREE) e-mail: customerservice@wfharris.com www.wfharrislighting.com

Form 1526 -LED 2/25

"A Live Operator Company Standing Ready to Serve Your Lighting Needs"

LED LAMP FIXTURE Ordering Information (Fill In Blanks For Complete Catalog Number)

Model	Lens Color	Bracket and Housing Color	Lamp	Options	Conduit Connection	
Model	Lens Color	Bracke Housing		Lamp	Options	Conduit Connections
¹ Provided B ² Housing Re ³ Dry Locatic ⁴ Interior Use	equired ons Only	HW- White HB- Bronz	e	LED	PC-Photo Control ² LL-Lens Lock 3H 1-1/2" Deep Housing (Specify Color) K-Black W-White B-Bronze D3H 3" Deep Housing (Specify Color) K-Black W-White B-Bronze GCO-Grounded Convenience Outlet ^{2,3} SW/B-On/Off Switch with Boot ^{2,4}	CRS-Right Side CLS-Left Side CT-Top CB-Bottom C4-All Four Sides (Positions Based on Facing Luminaire)



SBA QUALIFIED SMALL BUSINESS MANUFACTURER TRADE AGREEMENT ACT COMPLIANT

Specifications Subject to Change Without Notice

Luminaire is Warranted to be Free of Defects in Materials and Workmanship for One Year From Invoice Date.

LENS AND HOUSING CARRY A LIFETIME WARRANTY.

W_∃Harris Lighting, Inc.™

Innovative Lighting Designs Since 1970

P.O. Box 5023, Monroe, NC 28111-5023, USA 704.283.7477 (HEADQUARTERS) • 800.842.9345 (TOLL FREE) e-mail: customerservice@wfharris.com www.wfharrislighting.com

Printed in USA

Form 1526-LED

2/25

"W. F. Harris Lighting Will Not Sacrifice Quality for the Sake of Price."